

Margaret, Hardeman Co., Tex.

June 10, 1885.

John Wesley Esq.

I herewith submit
the following report of work done,
in retracing the base lines of
Block A. Hardeman Co., Tex. (original
work of W. & F.C.R.R. Co.)

Said report consists of the field
notes of said work, a description of
the method of doing said work, and
a sketch showing the lines run by
myself and their relations to the
lines of other surveys bearing on
part of the above work

July 2, 1885. Commencing at
the common corner of Survey 270, 271,
276 & 277 at an old stake which
was found by digging into the ground
and approximately corresponding to
the location of same corner from two
bearing trees with distances given,
and varying two feet from the stake
lately used by County Surveyor and
others as the true corner, from
said corner I ran a random line
using a variation of 11° E, six miles S.
Hence, turning a true right-angle

a'
with a railroad transit, I ran W. one mile. Found an original corner, as stone in ground with limbs of dead mesquite, looking very old, placed about the stone, the common block corner of Blocks A, B & E. Said corner agreeing in bearings and distance with two of the three given bearing trees. Said corner is common to Survey 264 & 265 Blk A. I then ran a random transit-line to west one mile. All of above lines are true transit-lines, and all measurements were made with a steel tape 100 feet long and of U.S. standard test. The greatest care being used in making the measurements to extent of using a plumb bob on uneven ground to ascertain the exact location of marking pin.

In comparing my first-random line to the S. with my last to the West. I found random line to S. 613 too far to W. Making necessary measurements from corner of the two random lines above mentioned to back sight, and making

necessary computations I located the true S.E. Cr. of Sur. 302 to the S.W. Cr. of Sur. No. 265, which also determined the true line from N.W.Cr. of Sur. No. 270 to S.E. Cr. of Sur. No. 302; also the true line from corner last-mentioned to the Common Block Corner aforesaid. Said two lines being at right angles to each other as shown by my transit.

This corner was located by bearing trees, etc. with distances given as shown in accompanying field notes.

I then returned to my commencing point

July 4. Commencing again at N.W. Cr. of Sur. 270. I produced the true line established to the Southward; Said line running in close proximity and to the W. of a line run a few wks. previously by W.J. Westmoreland and Mr. Armstrong starting from the same point. I crossed said line passing to the E. of it in a run of about one mile. At about 200' less than two miles from beginning point I found a stake established by Mr. Westmoreland, County Surveyor and accepted by ^{counter 22811} Westmoreland & Armstrong

a³

as the N.W.C. of Sur. No. 272. and N.E.
C. of Sur. No. 275. This corner was re-
ferred to a mesquite tree which was
claimed by the above named gentle-
men as the bearing tree shown in
field notes of cor. last mentioned.

This tree was carefully examined by
Judge Gordon, County Clerk J. Wesley,
myself and others, and with an eye
glance no indications could be found
to show this tree a bearing tree. We
all decided that it was not a bearing tree
the distance being so much short while
on the run of 6 miles to the S. we found
the distance of original work 1620 ft.
too great is another fact in favor of
our decision.

To the N. of the corner last-
mentioned, there being left on
the ground at this date no cor-
ners, bearings or distances of the
least reliability to fix the loca-
tion of the line or any of the sur-
vey section corners along said
line I continued my straight line
to the N.E. C. of Sur. No. 270 and
the N.W.C. of Sur. No. 277.

Geo H Chipman's 22.
Report on base line of B.I.K.
A. Dated June 10, 1885.

Front Co

12 9 14 5 20 10 00 00

counter 23842

Along said line I checked on some distant-bearing objects, as a grove of timber etc. shown in field note in County office (no distances given to certain existing objects) I allowed two ft. extra per mile to make good loss in measuring distances due to unevenness of ground and the inability of keeping the exact line in making the measurements.

At the corner last mentioned I established a corner as described in accompanying field notes.

We found the point located sometime previously by Mr. Westmoreland as the true corner last mentioned; which corner was 86 feet too far west of my line, (my line having crossed the line of Mr. Westmoreland again between N.W. C. of Sur. 270 & N.E. C. of Sur. 281

This corner of 270 as located by myself is about 150 ft. north of same corner as located by Mr. Westmoreland. We found, also, that the slate locating this corner, N.E. of Sur. No. 280 made

a⁵

by Mr. W. had been lately, within a few weeks, pulled up and carried E. 584; 8".

My line from the S.E.C. of Sur. 302 to N.E.C. of Sur. 280 of Blk. A is a true transit-line, probably not 4" out at any point.

Foard Co. St. File 21

John H. Dyer, Surveyor
Hardeman Co.
Tex

Foard

21

Sketch of Base Line
in Block A.

Geo H. Chipmanis

Description of
work done in re-
tracing the Base
Lines of Blk. A.

Hardeman Co.,
now Foard Co.
Tex.

Counter 22845